

شرکت فولاد کاوه جنوب کیش (سهامی عام)

شماره مناقصه T-1405134621



بسمه تعالی

موضوع مناقصه : تامین پکیج اقلام اتوماسیون برند ABB :

Item	Description	Qty	unit
1	رله تایمری TYPE: 1SVR 21V 00 R4100 TIME RELAY, TYPE: 1SVR 550 217 R4100, RATED CONTROL SUPPLY VOLTAGE: 24 VAC/DC AND 220-240 VAC, 1N/C AND 1N/O, F: 50/60 HZ, RATING CODE: B 300, 5A, TIME RANGE: 0.3-30 S, MOUNTING: DIN RAIL (IEC/EN 60715), PROTECTION HOUSING: IP50, PROTECTION TERMINALS: IP20, CONNECTING: 2 X 0.75-1.5 MM ² , TEMPERATURE: -20 TO +60 °C, CATEGORY: III, SINGLE-FUNCTION TIMER WITH STAR-DELTA CHANGE-OVER, IEC/EN 61812-1;	6	PCS
2	رله کنترل توان TYPE: RVC-10 POWER FACTOR CONTROLLER, TYPE: RVC-10, ORDER CODE: 2GCA288095A0050, OPERATING VOLTAGE: 100-440V, CURRENT INPUT: 1A OR 5A (RMS), MAX. CONTINUOUS CURRENT: 1.5 A, CAT. III RATED, NUMBER OF OUTPUTS: 10, CONNECTOR: SPRING CLAMP TERMINAL BLOCK, OPERATING TEMPERATURE: -10 TO 60° C, F: 50/60 HZ, IP40, DIMENSIONS: 144*144*80 MM;	2	PCS
3	راه انداز درایو TYPE: ACS-550-01-157A-4 VARIABLE SPEED DRIVE TYPE: ACS-550-01-157A-4_75KW ,400V,ABB	1	PCS
4	کارت منبع تغذیه مدل ۵۶۰ POWER SUPPLY UNIT FOR RTU560 RACKS , INPUT VOLTAGE 110...220 V DC , OUTPUT VOLTAGE 5 AND 24 V DC MODEL 560PSU01 , ABB	1	PCS
5	مبدل سیگنال TYPE: 1SVR011708R0400 SIGNAL CONVERTER, TYPE: 1SVR011708R0400, SUPPLY VOLTAGE (AC) 110-240, INPUT SIGNAL (A) 0-5 OR 0-20, OUTPUT SIGNAL (MA) 0-20 OR 4-20, OUTPUT SIGNAL (V) 0-10	6	PCS
6	به ابعاد ۹۵*۴۵ میلیمتر آمپر متر دیجیتال تابلویی ۱-۵ DIGITAL AMMETER, TYPE: EM100-I, SN: 101013000469, POWER SUPPLY: 85-265 VAC 85-256 VDC, V: 220/450 V AC	4	PCS
7	شمارنده TYPE: EM400 ENERGY METER FOR VOLTAGE, EM400-T(5A), POWER: 85-265 VAC, 5 W, WORK TEMP: -25 TO +70 °C, STORAGE TEMP: -30 TO +80°C, PANEL: IP50, HOUSING: IP 20, VOLTAGE: 220 VAC, CURRENT: 5A, OUT PUT: 4-20 MA, LOAD: 6002, ISOLATION VOLTAGE: 500 VDC, INTAREFACE: RS485, UPDATE SPEED: 3S , OUT PUT RELAY: 250V/5A OR 30 V/5A, SIZE: 96*96MM;	7	PCS
8	سوئیچ انتقال خودکار ولتاژ ۲۲۰ ولت AUTOMATIC TRANSFER SWITCH DEVICE MODEL: ATS021 , WITHOUT DIALOGO FOR CONTROLLER ON MULTI VOLTAGE ,AC230V,FREQUENCY:50, 60 HZ,IP20, PRODUCT ID: 1SDA065523R1,	2	PCS
9	منبع تغذیه TYPE : CP-E 24/5.0 POWER SUPPLY DEVICE, TYPE: CP-E 24/5.0, ORDER CODE: 1SVR 427 034 R0000, INPUT VOLTAGE RANGE : 90-132 V AC / 180-264 V AC/210-375 V DC, CURRENT: 24 V DC/5 A, INPUT CIRCUIT: L, N, F: 47-63 HZ, POWER: 140W, DISCHARGE CURRENT: 0.25 MA, OUTPUT VOLTAGE: 24 V DC, CAPACITIVE LOADS: 3500 MF, IP20, CLASS: I, TEMPERATURE: 35 TO +70 °C, DAMP HEAT: 95 % RH, STANDARD: EN 61204 3, DIMENSIONS : 63.2 X 123.6 X 123.6 MM;	3	PCS
10	منبع تغذیه TYPE: CP-E 24/10.0 POWER SUPPLY, TYPE: CP-E 24/10.0, ORDER CODE: 1SVR 427 035 R0000, INPUT VOLTAGE RANGE: 90-132VAC / 180-264 V AC / 210-375 V DC , / CURRENT: 24 V DC / 10 A	3	PCS
11	کارت کنترل TYPE: CP-A CM CONTROL MODULE, TYPE: CP-A CM, THE CP-A CM PROVIDES MONITORING OF THE INPUT SIGNALS OF THE REDUNDANCY UNIT CP-A RU, INPUT CIRCUITS - SUPPLY CIRCUITS: 1SVR 427 075 R0000, INPUT: 24 V DC, POWER: 1 W, CURRENT: 120 MA, OUTPUT VOLTAGE: 13- 28 V DC, OUTPUT CURRENT: 0.1 A, MATERIAL OF HOUSING: PLASTIC, HOUSING / TERMINALS: IP20, CLASS: II, TEMPERATURE: 25 TO +70 °C, DAMP HEAT: 93 % AT +40 °C, CLIMATIC CATEGORY: 3K3, DIMENSIONS: 56.5 X 54 X 24 MM;	2	PCS
12	منبع تغذیه TYPE: CP-E 24/20.0 POWER SUPPLY, TYPE: CP-E 24/20.0, ORDER CODE: 1SVR427036R0000, PRIMARY SWITCH MODE POWER SUPPLY, INPUT VOLTAGE RANGE: 90-264 VAC / 120-375 VDC, OUTPUT VOLTAGE / CURRENT: 24 VDC / 20 A, AMBIENT TEMPERATURE RANGE: -40...+55 °C	2	PCS
13	منبع تغذیه TYPE: CP-A RU POWER SUPPLY, TYPE: CP-A RU, THE CP-A RU PROVIDES DECOUPLING OF TWO CP POWER SUPPLY UNITS M 40 V AND M 5 A, ORDER CODE: 1SVR427071R0000, RATED INPUT VOLTAGE UIN: 24 V DC, INPUT VOLTAGE RANGE: 10-40 V DC, RATED OUTPUT VOLTAGE UOUT: 24 V DC, VOLTAGE DROP: TYP. 0.6 V, MAX. 0.9 V	2	PCS