

شرکت فولاد کاوه جنوب کیش (سهامی عام)

شماره مناقصه T-1405135163



بسمه تعالی

موضوع مناقصه: تامین کلید هوایی به همراه قطعات یدکی برند: SIEMENS

Item	Description	Qty	unit
1	کلید هوایی TYPE: 3WL1350-4CB66-5FA4-3P-5000A AIR CIRCUIT BREAKER, TYPE: 3WL1350-4CB66-5FA4, 3POLE, VOLTAGE: 690 VAC, CURRENT: 5000 A, F: 50/60 HZ, SIZE: 3, ICU: 100 KA AT 500 V, TRIP UNITS: LSI-ETU 25B, MOTORIZED OPERATING MECHANISM/110-127 VAC OR 110-125 VDC ACTIVATION 50/60 HZ, 1ST+2ND AUXILIARY SWITCH BLOCK: 4NO+4NC	1	PCS
2	کلید هوایی TYPE: 3WL1210-3CB66-5FA4-3P-1000A AIR CIRCUIT BREAKER, TYPE: 3WL1210-3CB66-5FA4, 3POLE, VOLTAGE: 690 VAC, CURRENT: 1000 A, F: 50/60 HZ, SIZE: 2, ICU: 85 KA AT 500 V, TRIP UNITS: LSI-ETU 25B, MOTORIZED OPERATING MECHANISM/110-127 VAC OR 110-125 VDC, 1ST+2ND AUXILIARY SWITCH BLOCK: 4NO+4NC	1	PCS
3	کلید هوایی TYPE: 3WL1216-3CB66-4GA4-3P-1600A AIR CIRCUIT BREAKER, TYPE: 3WL1216-3CB66-4GA4, 3POLE, VOLTAGE: 690 VAC, CURRENT: 1600 A, F: 50/60 HZ, SIZE: 2, ICU: 85 KA AT 500 V, TRIP UNITS: LSI-ETU 25B, MOTORIZED OPERATING MECHANISM/208-240 VAC 50/60 HZ/220-250 VDC, 1ST+2ND AUXILIARY SWITCH BLOCK: 4NO+4NC	1	PCS
4	کلید هوایی TYPE: 3WL1212-3CB66-4GA4-3P-1250A AIR CIRCUIT BREAKER, TYPE: 3WL1212-3CB66-4GA4, 3POLE, VOLTAGE: 690 VAC, CURRENT: 1250 A, F: 50/60 HZ, SIZE: 2, ICU: 85 KA AT 500 V, TRIP UNITS: LSI-ETU 25B, MOTORIZED OPERATING MECHANISM/208-240 VAC 50/60 HZ/220-250 VDC, 1ST+2ND AUXILIARY SWITCH BLOCK: 4NO+4NC	1	PCS
5	کلید هوایی TYPE: 3WL1208-3CB66-4GA4-3P-800A AIR CIRCUIT BREAKER, TYPE: 3WL1208-3CB66-4GA4, 3POLE, VOLTAGE: 690 VAC, CURRENT: 800 A, F: 50/60 HZ, SIZE: 2, ICU: 85 KA AT 500 V, TRIP UNITS: LSI-ETU 25B, MOTORIZED OPERATING MECHANISM/208-240 VAC 50/60 HZ/220-250 VDC, AUXILIARY SWITCH BLOCK: 4NO+4NC	1	PCS
6	کلید هوایی TYPE: 3WL1212-2CB66-4GA4-3P-1250A AIR CIRCUIT BREAKER, TYPE: 3WL1212-2CB66-4GA4, 3POLE, VOLTAGE: 690 VAC, CURRENT: 1250 A, F: 50/60 HZ, SIZE: 2, ICU: 66 KA AT 500 V, TRIP UNITS: LSI-ETU 25B, MOTORIZED OPERATING MECHANISM/208-240 VAC 50/60 HZ/220-250 VDC, AUXILIARY SWITCH BLOCK: 4NO+4NC	1	PCS
7	کلید هوایی TYPE: 3WL1232-2CB65-5FA4-3P-3200A AIR CIRCUIT BREAKER, TYPE: 3WL1232-2CB65-5FA4, 3POLE, VOLTAGE: 690 VAC, CURRENT: 3200 A, F: 50/60 HZ, ICU: 66 KA AT 500 V-ETU 25B, AUXILIARY SWITCH BLOCK: 4NO+4NC, MOTORIZED OPERATING MECHANISM: 110-127 VAC	1	PCS
8	رنگ دسته: خاکستری روشن، سری VL800 و VL630، متعلقات برای: کلیدهای اتوماتیک VL9600-3HF05 دسته کلید قدرت، نوع محصول: ۳، برند: زیمنس؛ HANDLE FOR POWER CIRCUIT BREAKER, PRODUCT TYPE: 3VL9600-3HF05, ACCESSORY FOR: VL630 AND VL800 CIRCUIT BREAKERS, HANDLE COLOR: LIGHT GRAY HANDLE, PRODUCT SERIES: SENTRON, BRAND: SIEMENS;	2	SET
9	سری محصول: AC، ولتاژ: ۱۱۰-۱۲۷ ولت، متعلقات برای: VL9800-1SR00، رله شنت، نوع محصول: ۳، برند: زیمنس؛ SHUNT RELEASE, PRODUCT TYPE: 3VL9800-1SR00, ACCESSORY FOR: VL630- VL800- VL1250- VL1600, VOLTAGE: 110-127 V AC, PRODUCT SERIES: SENTRON, BRAND: SIEMENS;	2	PCS
10	مناسب برای کلیدهای اتوماتیک: SENTRON، سری محصول: VL9800-2AE00، کیت کنتاکت کمکی و آلارم، نوع: ۳، کیت شامل: ۲ کنتاکت کمکی (۱ باز + ۱ بسته) و ۱ کنتاکت آلارم (۱ باز)، نصب: نصب در سمت چپ، ویژگی ها: قطعه یدکی فقط جهت تعویض و جایگزینی، برند: زیمنس؛ AUXILIARY AND ALARM SWITCH KIT, TYPE: 3VL9800-2AE00, PRODUCT SERIES: SENTRON, FOR CIRCUIT BREAKERS: VL630-VL800-VL1250-VL1600, KIT INCLUDES: 2 AUXILIARY SWITCHES (1 NO + 1 NC) AND 1 ALARM SWITCH (1 NO), MOUNTING: LEFT-SIDE MOUNTING, FEATURES: SPARE PART PRODUCT FOR REPLACEMENT PURPOSES ONLY, BRAND: SIEMENS	2	PCS

شرکت فولاد کاوه جنوب کیش (سهامی عام)

شماره مناقصه T-1405135163



11	فرکانس: ۶۰/۵۰ هرتز، اندازه کلید قابل نصب: AC، ولتاژ نامی تغذیه کنترلی: ۹۰-۱۱۰ ولت AC، نوع تغذیه کنترلی: RV2902-1DF0، رله شنت، نوع: ۳، ابعاد (عرض×ارتفاع×عمق): ۱۹×۹۰×۶۸ میلی متر، درجه حفاظت: SNAP-ON، مقدار ولتاژ عایقی نامی: ۶۹۰ ولت، نوع نصب: S00-S0-S2-S3، SIEMENS، برند: IP20 SHUNT RELEASE, TYPE: 3RV2902-1DF0, CONTROL SUPPLY TYPE: AC, RATED CONTROL VOLTAGE: 90-110 V AC, FREQUENCY: 50/60 HZ, SIZE OF BREAKER SIZE: S00-S2-S3, INSULATION VOLTAGE RATED VALUE: 690 V, MOUNTING TYPE: SNAP-ON, DIMENSION (W×H×D): 19×90×68 MM, DEGREE OF PROTECTION: IP20, BRAND: SIEMENS;	3	PCS
12	TYPE: 3WL1340-4EG36-5FA4-Z-3P-4000A WITHDRAWABLE CIRCUIT BREAKER, TYPE: 3WL1340-4EG36-5FA4-Z, WITH GUIDE FRAME, 3POLE, SIZE: III, IEC IN: 4000A TO 690V, AC50/60HZ	1	PCS
13	TYPE: 3WL9111-0AH12-0AA0 AIR CIRCUIT BREAKER POSITION SIGNALING SWITCH FOR GUIDE FRAME, TYPE: 3WL9111-0AH12-0AA0, VERSION: R16 2ND BLOCK/6 CO CONTACTS	2	PCS
14	TYPE: 3VA9988-0AB12 TRIP ALARM SWITCH CHANGEOVER CONTACTS, TYPE: 3VA9988-0AB12, HQ 7MM UE: 240VAC/50HZ, 250VDC, ITH: 6A, UIMP: 4KV, UI: 690V, ACCESSORY FOR 3VA1 AND 3VA20 UP TO 3VA25	2	PCS
15	TYPE: 3WL9111-0AP01-0AA0 AIR CIRCUIT BREAKER DOOR SEALING FRAM, TYPE: 3WL9111-0AP01-0AA0, SPARE PART FOR OPTION T40	2	PCS
16	TYPE: 3VA9987-0KB00 POSITION SIGNALING SWITCH, TYPE: 3VA9987-0KB00, UI: 240V, UIMP: 4KV, UE: 240VAC/50HZ, 250VDC, I: 6A, ACCESSORY FOR PLUG-IN & DRAW-OUT UNIT	2	PCS
17	TYPE: 3VA9987-0KD80 AUXILIARY CIRCUIT CONNECTOR, TYPE: 3VA9987-0KD80, UE: 500VAC/50HZ, 250VDC, UIMP: 4KV, ITH: 10A, UI: 500V, HEIGHT: 88MM, ACCESSORY FOR: ALL 3VA/DRAW-OUT UNITS-SIEMENS	2	PCS
18	TYPE: 3VA9467-0HA20 MOTORIZED OPERATING MECHANISM OF CIRCUIT BREAKER, TYPE: 3VA9467-0HA20, 110-230V AC/110-250V DC ACCESSORY FOR: 3VA1-400/630, 3VA2- 400/630	3	PCS
19	TYPE: 3WL9111-0AH01-0AA0 AIR CIRCUIT BREAKER READY TO CLOSE SIGNALING SWITCH, TYPE: 3WL9111-0AH01-0AA0, CONTACT: 1 NO	2	PCS
20	TYPE: 3VA9267-0HA20 MOTORIZED OPERATING MECHANISM OF CIRCUIT BREAKER, TYPE: 3VA9267-0HA20, 110-230V AC/110-250V DC, ACCESSORY FOR: 3VA2(100/160/250A)	2	PCS
21	TYPE: 3VA9988-0BL32 SHUNT TRIP RELAY, TYPE: 3VA9988-0BL32, VOLTAGE: 110-127 VAC, F: 50/60 HZ, APPARENT POWER CONSUMPTION: 40 VA, DC CONSUMED ACTIVE POWER: 40 W, RATED INSULATION VOLTAGE: 690 V, SURGE VOLTAGE RESISTANCE: 4 KV, ACCESSORY FOR 3VA1 AND 3VA20 UP TO 3VA25	1	PCS
22	TYPE: 3VA9987-0KD81 CRANK HANDLE ACCESSORY FOR DRAW OUT UNIT, TYPE: 3VA9987-0KD81	2	PCS
23	TYPE: 3VA9323-0KD00 DRAW-OUT UNIT COMPLETE KIT, TYPE: 3VA9323-0KD00, ACCESSORY FOR CB 3POLE 3VA1-400/630, 3VA2- 400/630	2	PCS
24	TYPE: 3WL9111-0AH14-0AA0 AIR CIRCUIT BREAKER TRIPPED SIGNALING SWITCH, TYPE: 3WL9111-0AH14-0AA0, CONTACT: 1 CO	2	PCS